

# LRD32

thermal overload relay for motor TeSys -  
23...32 A - class 10A



## Main

Range of product	TeSys D
Device short name	LRD
Product or component type	Differential thermal overload relay
Relay application	Motor protection
Product compatibility	LC1D25...LC1D38 LC1D32
Network type	AC
Overload tripping class	Class 10A conforming to IEC 60947-4-1
Thermal protection adjustment range	23...32 A
Protection type	AM fuses 40 A - for power circuit BS fuse 5 A - for control circuit BS88 fuse 63 A - for power circuit GB2 circuit breaker 5 A - for control circuit GG fuse 5 A - for control circuit GG fuse 63 A - for power circuit
[Ui] rated insulation voltage	1000 V power circuit conforming to IEC 60947-4-1 600 V power circuit conforming to CSA 600 V power circuit conforming to UL
Connections - terminals	Screw clamp terminals control circuit: 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamp terminals control circuit: 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screw clamp terminals control circuit: 1 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end Screw clamp terminals control circuit: 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamp terminals control circuit: 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screw clamp terminals control circuit: 2 cable 1...2.5 mm <sup>2</sup> - cable stiffness: solid - without cable end Screw clamp terminals power circuit: 1 cable 4...35 mm <sup>2</sup> - cable stiffness: flexible - with cable end Screw clamp terminals power circuit: 1 cable 4...35 mm <sup>2</sup> - cable stiffness: flexible - without cable end Screw clamp terminals power circuit: 1 cable 4...35 mm <sup>2</sup> - cable stiffness: solid - without cable end
Quantity per set	Set of 10

## Complementary

Network frequency	<= 400 Hz
Mounting support	Under contactor
Tripping threshold	1.14 +/- 0.06 I <sub>r</sub> conforming to IEC 60947-4-1
Surge withstand	6 kV conforming to IEC 60801-5
[I <sub>th</sub> ] conventional free air thermal current	5 A for control circuit
[U <sub>e</sub> ] rated operational voltage	1000 V AC 50/60 Hz for power circuit conforming to IEC 60947-4-1
[U <sub>imp</sub> ] rated impulse withstand voltage	6 kV
Phase failure sensitivity	Tripping current I 30 % of I <sub>r</sub> on one phase, the others at I <sub>r</sub> conforming to IEC 60947-4-1
Reset	Automatic reset Manual reset
Temperature compensation	-20...60 °C
Tightening torque	1.7 N.m control circuit: - on screw clamp terminals 5 N.m power circuit: - on screw clamp terminals 8 N.m power circuit: - on screw clamp terminals
Height	80 mm

Width	45 mm
Depth	66 mm
Product weight	0.124 kg

## Environment

Standards	CSA C22-2 No 14 Directive ATEX 94/9/EC EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	ATEX INERIS BV CCC CSA GOST RINA UL
Protective treatment	TH conforming to IEC 60068
IP degree of protection	IP2x conforming to VDE 0106
Ambient air temperature for operation	-20...60 °C without derating conforming to IEC 60947-4-1 -40...70 °C with derating conforming to IEC 60947-4-1
Ambient air temperature for storage	-60...70 °C
Fire resistance	850 °C conforming to IEC 60695-2-1
Shock resistance	15 gn 11 ms conforming to IEC 60068-2-7
Vibration resistance	6 gn conforming to IEC 60068-2-6
Dielectric strength	6 kV at 50 Hz conforming to IEC 60255-5