



ANTI SEIZE COMPOUND

Pasta antiagarrotamiento basada en cobre para todo tipo de pasadores y mecanismos estáticos.

Anti Seize Compound es un lubricante de montaje y antiagarrotamiento que impide la adherencia y el agarrotamiento incluso en condiciones húmedas, sucias y corrosivas.

CARACTERÍSTICAS

- Ø Margen de temperatura -10°C a 1100°C
- Ø Impide la adherencia y el agarrotamiento de los pasadores de rosca estáticos
- Ø Lubrica, protege y facilita el desmontaje
- Ø Eficaz incluso en los entornos más agresivos
- Ø Insoluble en agua
- Ø Ideal para hornos, sistemas de escape y aplicaciones en muelles de carga y plataformas petrolíferas

INSTRUCCIONES DE USO

- Ø Aplíquese como película fina con un pincel o un trapo sobre una superficie seca y limpia.
- Ø Para obtener los mejores resultados, aplíquese igualmente sobre piezas machos y hembras.

Las fichas de datos técnicos y de seguridad pueden obtenerse en:

Servicio de fax : +44 (0)113 232 2770
Sitio Web : www.rocol.com
Servicio de atención al cliente : +44 (0)113 232 2700

Issue 1403d: 09/06/03

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

www.rocolshop.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

T
E
C
H
N
I
C
A
L

D
A
T
A



ANTI SEIZE COMPOUND

DATOS TÉCNICOS (valores característicos)

Aspecto	Pasta de color cobre oscuro
NLGI No. (IP 50) (ASTM D217)	NLGI No. 1/2
Tipo de base	Aceite mineral
Espesante	Arcilla orgánicamente modificada
Sólidos	Cobre, grafito, MoS ₂
Contenido de sólidos	Aproximadamente 37%
Margen de temperatura	-10 ⁰ C a 1100 ⁰ C
Solubilidad en agua	Insoluble
Cobertura aproximada	5m ² /kg
Especificaciones	
Catálogo Naval N°	0475-541-8659 (6kg)
Ref RAF N°	34D/301-6210 (85g) 34D/224-6794 (500g)
N° de catálogo OTAN	8030-99-301-6210 (85g) 8030-99-224-6794 (500g) 8030-99-541-8659 (6kg)
Almacenamiento	La temperatura de almacenamiento debe controlarse entre 1°C y 40°C.
Tamaños de envase	85g, 500g, 6kg, 18kg

Issue 1403d: 09/06/03

2

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

www.rocolshop.com

ROCOL is a BS EN ISO 9001 registered company.
ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

TECHNICAL DATA



ANTI SEIZE COMPOUND

Issue 1403d: 09/06/03

3

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: +44 (0)113 232 2600 Fax: +44 (0)113 232 2760

www.rocol.com

www.rocolshop.com

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW Inc.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.