

# SAFETY DATA SHEET

ARALDITE® WOOD REPAIR RESIN

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : ARALDITE® WOOD REPAIR RESIN  
**Product code** : 00073826  
**Product description** :

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Resin for adhesive systems

### 1.3 Details of the supplier of the safety data sheet

**Supplier** : Huntsman Advanced Materials (Europe)BVBA  
Everslaan 45  
3078 Everberg / Belgium  
Tel.: +41 61 299 20 41  
Fax: +41 61 299 20 40

**e-mail address of person responsible for this SDS** : Global\_Product\_EHS\_AdMat@huntsman.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
India: +91 22 4050 6333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : R10  
Xn; R20  
Xi; R36/38

**Physical/chemical hazards** : Flammable.

**Human health hazards** : Harmful by inhalation. Irritating to eyes and skin.


See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

<b>ARALDITE WOOD REPAIR RESIN</b>				<b>2/15</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

**SECTION 2: Hazards identification**

**Hazard symbol or symbols** : 

**Indication of danger** : Harmful

**Risk phrases** : R10- Flammable.  
R20- Harmful by inhalation.  
R36/38- Irritating to eyes and skin.

**Safety phrases** : S2- Keep out of the reach of children.  
S16- Keep away from sources of ignition - No smoking.  
S23- Do not breathe vapour or spray.  
S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37- Wear suitable gloves.  
S46- If swallowed, seek medical advice immediately and show this container or label.

**Hazardous ingredients** : Styrene

**Supplemental label elements** : Not applicable.

Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Yes, applicable.

**2.3 Other hazards**

**Other hazards which do not result in classification** : Not available.

**SECTION 3: Composition/information on ingredients**

**Substance/mixture** : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	

<b>ARALDITE WOOD REPAIR RESIN</b>				<b>3/15</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

### SECTION 3: Composition/information on ingredients

Styrene	CAS: 100-42-5 EC: 202-851-5	30-60	R10 Xn; R20 Xi; R36/38  <b>See Section 16 for the full text of the R-phrases declared above.</b>	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335i STOT RE 1, H372i Asp. Tox. 1, H304  <b>See Section 16 for the full text of the H statements declared above.</b>	[1][2]
---------	--------------------------------	-------	--	---	--------

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Irritating to eyes.
- Inhalation** : Harmful by inhalation.
- Skin contact** : Irritating to skin.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

**ARALDITE WOOD REPAIR RESIN**

**4/15**

<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1

**SECTION 4: First aid measures**

- Eye contact** : Adverse symptoms may include the following:  
irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

**5.3 Advice for firefighters**

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

**ARALDITE WOOD REPAIR RESIN**

5/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 6: Accidental release measures**

**6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**6.3 Methods and materials for containment and cleaning up**

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.  
 Not applicable.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental

**ARALDITE WOOD REPAIR RESIN**

6/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 7: Handling and storage**

contamination.

**Storage hazard class** : Storage class 3, Flammable liquids  
**Huntsman Advanced Materials**

**7.3 Specific end use(s)**

**Recommendations** : Not available.  
**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**

Occupational exposure limits

Product/ingredient name	Exposure limit values
styrene	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> STEL: 250 ppm 15 minute(s). TWA: 100 ppm 8 hour(s). TWA: 430 mg/m <sup>3</sup> 8 hour(s). STEL: 1080 mg/m <sup>3</sup> 15 minute(s).

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
Styrene	DNEL	Short term Inhalation	289 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	306 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	406 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	85 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	174.25 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Short term Inhalation	182.75 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Long term Dermal	343 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	10.2 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	2.1 mg/kg bw/day	Consumers	Systemic

Predicted effect concentrations

**ARALDITE WOOD REPAIR RESIN**

7/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
Styrene	PNEC	Fresh water	0.028 mg/l	-
	PNEC	Marine	0.0028 mg/l	-
	PNEC	PNECintermittent	0.04 mg/l	-
	PNEC	Sewage Treatment Plant	5 mg/l	-
	PNEC	Fresh water sediment	0.614 mg/kg	-
	PNEC	Marine water sediment	0.0614 mg/kg	-
	PNEC	Soil	0.2 mg/kg	-

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Material of gloves for long term application (BTT>480min):** : butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL), nitrile rubber, neoprene, Polyvinyl Chloride (PVC)

**Material of gloves for short term/splash application (10min<BTT<480min):** : butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL), nitrile rubber, neoprene, Polyvinyl Chloride (PVC)

(BTT = Break Through Time)

Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Additional information can be found for instance at [www.gisbau.de](http://www.gisbau.de).

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**ARALDITE WOOD REPAIR RESIN**

**8/15**

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 8: Exposure controls/personal protection**

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance

**Physical state** : Liquid.  
**Colour** : Yellow.  
**Odour** : Solvent  
**Odour threshold** : Not available.  
**pH** : Not available.  
**Melting point/freezing point** : Not available.  
**Initial boiling point and boiling range** : 145°C  
**Flash point** : Closed cup: 32°C [DIN 53213]  
**Evaporation rate** : Not available.  
**Flammability (solid, gas)** : Not available.  
**Burning time** : Not applicable.  
**Burning rate** : Not applicable.  
**Upper/lower flammability or explosive limits** : Lower: 1.1%  
Upper: 8.9%  
**Vapour pressure** : 0.7 kPa [20°C]  
**Vapour density** : Not available.  
**Relative density** : Not available.  
**Solubility(ies)**  
**Water solubility** : Not miscible  
  
**Partition coefficient: n-octanol/water (LogK<sub>ow</sub>)** : Not available.  
**Auto-ignition temperature** : 425°C  
**Decomposition temperature** : Not available.  
**Viscosity** : Dynamic: 825 mPa·s 23 deg C  
**Explosive properties** : Not available.  
**Oxidising properties** : Not available.

**9.2 Other information**

**Density** : 1.11 g/cm<sup>3</sup>

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**ARALDITE WOOD REPAIR RESIN**

9/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 10: Stability and reactivity**

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

Acute toxicity

Product/ingredient name	Endpoint	Species	Result	Exposure
ARALDITE WOOD REPAIR RESIN	LD50 Oral	Rat	>2000 mg/kg	-
Styrene	LC50 Inhalation Vapour	Rat	11.8 mg/L	4 hours
	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
	LD50 Oral	Rat - Male, Female	5000 mg/kg	-

Irritation/Corrosion

**Conclusion/Summary**

**Skin** : No additional information.  
**Eyes** : No additional information.  
**Respiratory** : No additional information.

Sensitiser

Product/ingredient name	Test	Route of exposure	Species	Result
Styrene	-	skin	Guinea pig	Not sensitizing

**Conclusion/Summary** : No additional information.

Mutagenicity

Product/ingredient name	Test	Result
Styrene	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Positive
	OECD 479 Genetic Toxicology: In vitro Sister Chromatid Exchange Assay in Mammalian Cells	Positive
	OECD 471 Bacterial Reverse Mutation Test	Negative
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Negative
	OECD 486 Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo	Negative

Carcinogenicity

Product/ingredient name	Test	Species	Exposure	Result	Route of exposure	Target organs

<b>ARALDITE WOOD REPAIR RESIN</b>				<b>10/15</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

**SECTION 11: Toxicological information**

Styrene	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	Mouse	104 weeks; 6 hours per day	Positive	Inhalation	lungs
	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	Rat	104 weeks; 6 hours per day	Negative	Inhalation	-

Reproductive toxicity

Product/ingredient name	Test	Species	Result/Result type	Target organs
Styrene	OECD 416 Two-Generation Reproduction Toxicity Study	Rat	Inhalation: 640 mg/m3 NOAEL	-

Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
Styrene	OECD 414 Prenatal Developmental Toxicity Study	Rat	2556 mg/m3 NOAEL

**Information on the likely routes of exposure** : Not available.

Potential acute health effects

- Inhalation** : Harmful by inhalation.
- Ingestion** : Irritating to mouth, throat and stomach.
- Skin contact** : Irritating to skin.
- Eye contact** : Irritating to eyes.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : No specific data.
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Eye contact** : Adverse symptoms may include the following:  
irritation  
watering  
redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Product/ingredient name	Test	Result type	Result	Target organs

**ARALDITE WOOD REPAIR RESIN**

11/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 11: Toxicological information**

Styrene	-	NOAEL -	1000 mg/kg/d	stomach
	-	NOAEL	150 mg/kg/d	-
	-	NOAEL	10 mg/kg/d	lungs
	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	LOEC Vapour	210 mg/m3	nose/sinuses

**Conclusion/Summary** : Not available.  
**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**IARC** : Styrene 2B  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.  
**Other information** : Not available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Styrene	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	30 minutes Static	Bacteria	500 mg/L
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours Flow-through	Daphnia	4.7 mg/L
	EPA OPPTS EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)	Acute ErC50 (growth rate)	96 hours Static	Algae	6.3 mg/L
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Flow-through	Fish	10 mg/L
	EPA OPPTS EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)	Chronic LOAEL	96 hours Static	Algae	0.28 mg/L
	OECD 211 <i>Daphnia</i> Magna Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	1.01 mg/L

**12.2 Persistence and degradability**

Product/ingredient name	Test	Period	Result
Styrene	ISO ISO DIS 9408	28 days	70.9 %

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Styrene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Styrene	2.96	74	low

<b>ARALDITE WOOD REPAIR RESIN</b>				<b>12/15</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

## SECTION 12: Ecological information

### 12.4 Mobility in soil

- Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.
- Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

Not applicable.

- 12.6 Other adverse effects** : No known significant effects or critical hazards.

### 12.7 Other ecological information

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

- Hazardous waste** : Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation
07 02 08*	other still bottoms and reaction residues

#### Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.




**ARALDITE WOOD REPAIR RESIN**

13/15

**Date of printing** : 13 August 2012 **MSDS no.** : 00073826  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 14: Transport information**

	14.1 UN number	14.2 UN proper shipping name
<b>ADR/RID</b>	UN1866	RESIN SOLUTION
<b>IMDG</b>	UN1866	RESIN SOLUTION
<b>IATA</b>	UN1866	RESIN SOLUTION

	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards	14.6 Special precautions for user	Additional information
<b>ADR/RID</b>	3 	III	No.	Not available.	<b>Hazard identification number</b> 30 <b>Special provisions</b> 640E <b>Tunnel code</b> D/E
<b>IMDG</b>	3 	III	No.	Not available.	<b>Emergency schedules (EmS)</b> F-E, _S-E_
<b>IATA</b>	3 	III	No.	Not available.	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 60 L Packaging instructions: 355 <b>Cargo Aircraft Only</b> Quantity limitation: 220 L Packaging instructions: 366

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not applicable.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

<b>ARALDITE WOOD REPAIR RESIN</b>				<b>14/15</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

## SECTION 15: Regulatory information

### Other EU regulations

- Europe inventory** : All components are listed or exempted.
- Black List Chemicals** : Not listed
- Priority List Chemicals** : Listed
- Integrated pollution prevention and control list (IPPC) - Air** : Not listed
- Integrated pollution prevention and control list (IPPC) - Water** : Not listed

### National regulations

- References** : The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974.

### International regulations

- Chemical Weapons Convention List Schedule I Chemicals** : Not listed
- Chemical Weapons Convention List Schedule II Chemicals** : Not listed
- Chemical Weapons Convention List Schedule III Chemicals** : Not listed

- 15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

➤ Indicates information that has changed from previously issued version.

- Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226  
 Skin Irrit. 2, H315  
 Eye Irrit. 2, H319  
 STOT SE 3, H335i  
 STOT RE 1, H372i

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335i STOT RE 1, H372i	On basis of test data Calculation method Calculation method Calculation method Calculation method

<b>ARALDITE WOOD REPAIR RESIN</b>		<b>15/15</b>	
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073826
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1

**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335i May cause respiratory irritation. H372i Causes damage to organs through prolonged or repeated exposure if inhaled.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2 STOT RE 1, H372i SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): INHALATION - Category 1  STOT SE 3, H335i SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): INHALATION [Respiratory tract irritation] - Category 3
<b>Full text of abbreviated R phrases</b>	: R10- Flammable. R20- Harmful by inhalation. R36/38- Irritating to eyes and skin.
<b>Full text of classifications [DSD/DPD]</b>	: Xn - Harmful Xi - Irritant
<b>MSDS no.</b>	: 00073826
<b>Date of printing</b>	: 8/13/2012.
<b>Date of issue/ Date of revision</b>	: 8/13/2012.
<b>Date of previous issue</b>	: No previous validation.
<b>Version</b>	: 1

**Notice to reader**

*While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.*

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

*Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.*

ARALDITE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.**

# SAFETY DATA SHEET

## ARALDITE® WOOD REPAIR POWDER

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : ARALDITE® WOOD REPAIR POWDER  
**Product code** : 00073827  
**Product description** :

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Hardener for adhesive systems

#### 1.3 Details of the supplier of the safety data sheet

**Supplier** : Huntsman Advanced Materials (Europe)BVBA  
Everslaan 45  
3078 Everberg / Belgium  
Tel.: +41 61 299 20 41  
Fax: +41 61 299 20 40

**e-mail address of person responsible for this SDS** : Global\_Product\_EHS\_AdMat@huntsman.com

#### 1.4 Emergency telephone number

##### Supplier

**Telephone number** : EUROPE: +32 35 75 1234  
France ORFILA: +33(0)145425959  
ASIA: +65 6336-6011  
China: +86 20 39377888  
India: +91 22 4050 6333  
Australia: 1800 786 152  
New Zealand: 0800 767 437  
USA: +1/800/424.9300

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : R43

**Human health hazards** : May cause sensitisation by skin contact.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard symbol or symbols** :



**Indication of danger** : Irritant

**Risk phrases** : R43- May cause sensitisation by skin contact.

<b>ARALDITE WOOD REPAIR POWDER</b>				<b>2/14</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

**SECTION 2: Hazards identification**

**Safety phrases** : S2- Keep out of the reach of children.  
 S3/7- Keep container tightly closed in a cool place.  
 S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.  
 S46- If swallowed, seek medical advice immediately and show this container or label.

**Hazardous ingredients** : dibenzoyl peroxide

**Supplemental label elements** : Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

**2.3 Other hazards**

**Other hazards which do not result in classification** : Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat. Fine dust clouds may form explosive mixtures with air.

**SECTION 3: Composition/information on ingredients**

**Substance/mixture** : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
barium sulphate, natural	CAS: 7727-43-7 EC: 231-784-4	30-60	Not classified.	Not classified.	[2]
Limestone	CAS: 1317-65-3 EC: 215-279-6	13-30	Not classified.	Not classified.	[2]
dibenzoyl peroxide	CAS: 94-36-0 EC: 202-327-6	1-3	E; R3 O; R7 Xi; R36 R43 N; R50	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400	[1]
silicon dioxide, chemically prepared	CAS: 7631-86-9 EC: 231-545-4	1-3	Not classified.  <b>See Section 16 for the full text of the R-phrases declared above.</b>	Not classified.  <b>See Section 16 for the full text of the H statements declared above.</b>	-

Type

**ARALDITE WOOD REPAIR POWDER**

**3/14**

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 3: Composition/information on ingredients**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

Potential acute health effects

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : May cause sensitisation by skin contact.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**ARALDITE WOOD REPAIR POWDER**

4/14

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 4: First aid measures**

**Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
**Specific treatments** : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media** : Use dry chemical powder.  
**Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Fine dust clouds may form explosive mixtures with air.  
**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 sulfur oxides  
 metal oxide/oxides

**5.3 Advice for firefighters**

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.  
**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.  
**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

**6.2 Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**6.3 Methods and materials for containment and cleaning up**

**ARALDITE WOOD REPAIR POWDER**

5/14

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 6: Accidental release measures**

- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
 See Section 8 for information on appropriate personal protective equipment.  
 See Section 13 for additional waste treatment information.

**SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**7.1 Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.  
  
 Not applicable.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

- : Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**Storage hazard class Huntsman Advanced Materials**

- : Storage class 13, Solid materials, not dangerous

**7.3 Specific end use(s)**

- Recommendations** : Not available.

**ARALDITE WOOD REPAIR POWDER**

6/14

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 7: Handling and storage**

**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**

Occupational exposure limits

Product/ingredient name	Exposure limit values
barium sulphate, natural	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 10 mg/m <sup>3</sup> 8 hour(s). Form: inhalable dust TWA: 4 mg/m <sup>3</sup> 8 hour(s). Form: respirable dust
Limestone	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 10 mg/m <sup>3</sup> 8 hour(s). Form: inhalable dust TWA: 4 mg/m <sup>3</sup> 8 hour(s). Form: respirable dust
silicon dioxide, chemically prepared	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007).</b> TWA: 6 mg/m <sup>3</sup> 8 hour(s). Form: inhalable dust TWA: 2.4 mg/m <sup>3</sup> 8 hour(s). Form: respirable dust

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**ARALDITE WOOD REPAIR POWDER**

7/14

<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1

**SECTION 8: Exposure controls/personal protection**

- Material of gloves for long term application (BTT>480min):** : butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL), nitrile rubber, neoprene, Polyvinyl Chloride (PVC)
- Material of gloves for short term/splash application (10min<BTT<480min):** : butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL), nitrile rubber, neoprene, Polyvinyl Chloride (PVC)

(BTT = Break Through Time)

Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Additional information can be found for instance at [www.gisbau.de](http://www.gisbau.de).

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance

- Physical state** : Solid. [Powder.]
- Colour** : Grey.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Not available.
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Burning time** : Not available.
- Burning rate** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : Not available.
- Solubility(ies)** : Not available.

<b>ARALDITE WOOD REPAIR POWDER</b>				<b>8/14</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

## SECTION 9: Physical and chemical properties

**Water solubility** : Not miscible

**Partition coefficient: n-octanol/water (LogK<sub>ow</sub>)** : Not available.

**Auto-ignition temperature** : Not available.

**Decomposition temperature** : Not available.

**Viscosity** : Not available.

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### 9.2 Other information

**Density** : 0.85 g/cm<sup>3</sup>

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

Reacts violently in contact with acids, amines, polymerization accelerators and easily oxidized materials

**10.4 Conditions to avoid** : Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.

**10.5 Incompatible materials** : acids, reducing agents, heavy metals, bases, iron, copper, rust

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Decomposition products may include the following materials: Burning produces obnoxious and toxic fumes., Carbon oxides

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Endpoint	Species	Result	Exposure
barium sulphate, natural dibenzoyl peroxide	LD50 Oral	Rat - Male	307 to 364 g/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male	>24.3 mg/L	4 hours
	LD50 Oral	Mouse - Male, Female	>2000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Test	Species	Route of exposure	Result

**ARALDITE WOOD REPAIR POWDER**

9/14

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 11: Toxicological information**

barium sulphate, natural	- OECD 405 Acute Eye Irritation/Corrosion No official guidelines	Rat Rabbit	Respiratory Eyes	Irritant Non-irritant.
dibenzoyl peroxide	OECD 405 Acute Eye Irritation/Corrosion OECD 404 Acute Dermal Irritation/Corrosion	Human skin model Rabbit Rabbit	Skin Eyes Skin	Non-irritant. Irritant Non-irritant.

**Conclusion/Summary**

**Skin** : No additional information.  
**Eyes** : No additional information.  
**Respiratory** : No additional information.

**Sensitiser**

Product/ingredient name	Test	Route of exposure	Species	Result
barium sulphate, natural	OECD 429 Skin Sensitisation: Local Lymph Node Assay	skin	Mouse	Not sensitizing
dibenzoyl peroxide	OECD 429 Skin Sensitisation: Local Lymph Node Assay	skin	Mouse	Sensitising

**Conclusion/Summary** : No additional information.

**Mutagenicity**

Product/ingredient name	Test	Result
barium sulphate, natural	OECD 471 Bacterial Reverse Mutation Test	Negative
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Negative
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Negative
dibenzoyl peroxide	OECD 471 Bacterial Reverse Mutation Test	Negative
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Negative
	OECD 478 Genetic Toxicology: Rodent Dominant Lethal Test	Negative
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Negative

**Carcinogenicity**

Product/ingredient name	Test	Species	Exposure	Result	Route of exposure	Target organs
barium sulphate, natural	EPA OPPTS	Mouse	0 weeks	Negative	Oral	-
	EPA OPPTS	Rat	104 weeks	Negative	Oral	-
dibenzoyl peroxide	No official guidelines	Mouse	104 weeks	Negative	Dermal	-

**Reproductive toxicity**

Product/ingredient name	Test	Species	Result/Result type	Target organs

<b>ARALDITE WOOD REPAIR POWDER</b>				<b>10/14</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

## SECTION 11: Toxicological information

dibenzoyl peroxide	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	-
--------------------	--	-----	------	---

### Teratogenicity

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : May cause sensitisation by skin contact.
- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Ingestion** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Product/ingredient name	Test	Result type	Result	Target organs
barium sulphate, natural	-	NOAEL -	>104 mg/kg	kidneys
	-	LOEC Dusts and mists	40 mg/m3	lungs
dibenzoyl peroxide	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	NOAEL -	1000 mg/kg	-

- Conclusion/Summary** : Not available.
- General** : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.

**ARALDITE WOOD REPAIR POWDER**

11/14

**Date of printing** : 13 August 2012 **MSDS no.** : 00073827  
**Date of issue** : 13 August 2012 **Version** : 1

**SECTION 11: Toxicological information**

**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.  
**Other information** : Not available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
barium sulphate, natural	OECD 201 Alga, Growth Inhibition Test	Acute EC50	72 hours Static	Algae	>100 mg/L
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute LC50	48 hours Static	Daphnia	14.5 mg/L
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	174 mg/L
	OECD 211 <i>Daphnia</i> Magna Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	5.8 mg/L
dibenzoyl peroxide	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50	30 minutes Static	Bacteria	35 mg/L
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours Static	Daphnia	0.11 mg/L
	OECD 201 Alga, Growth Inhibition Test	Acute EbC50 (biomass)	72 hours Static	Algae	0.0422 mg/L
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Semi-static	Fish	0.0602 mg/L

**12.2 Persistence and degradability**

Product/ingredient name	Test	Period	Result
dibenzoyl peroxide	OECD 301D Ready Biodegradability - Closed Bottle Test	28 days	68 %

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
dibenzoyl peroxide	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
dibenzoyl peroxide	3.2	-	high

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.  
**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**12.7 Other ecological information**

<b>ARALDITE WOOD REPAIR POWDER</b>				<b>12/14</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

### SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**Hazardous waste** : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
07 02 08*	other still bottoms and reaction residues

Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### SECTION 14: Transport information

	14.1 UN number	14.2 UN proper shipping name
<b>ADR/RID</b>	Not regulated.	-
<b>IMDG</b>	Not regulated.	-
<b>IATA</b>	Not regulated.	-

	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards	14.6 Special precautions for user	Additional information
<b>ADR/RID</b>	-	-	No.	Not available.	-
<b>IMDG</b>	-	-	No.	Not available.	-
<b>IATA</b>	-	-	No.	Not available.	-

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not applicable.

<b>ARALDITE WOOD REPAIR POWDER</b>		<b>13/14</b>	
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

##### Other EU regulations

**Europe inventory** : All components are listed or exempted.

**Black List Chemicals** : Not listed

**Priority List Chemicals** : Not listed

**Integrated pollution prevention and control list (IPPC) - Air** : Not listed

**Integrated pollution prevention and control list (IPPC) - Water** : Not listed

##### National regulations

**References** : The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974.

##### International regulations

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed

**Chemical Weapons Convention List Schedule II Chemicals** : Not listed

**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

📌 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

<b>ARALDITE WOOD REPAIR POWDER</b>				<b>14/14</b>
<b>Date of printing</b>	: 13 August 2012	<b>MSDS no.</b>	: 00073827	
<b>Date of issue</b>	: 13 August 2012	<b>Version</b>	: 1	

**SECTION 16: Other information**

Classification	Justification
Skin Sens. 1, H317	Calculation method

- Full text of abbreviated H statements** : H241 Heating may cause a fire or explosion.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H400 Very toxic to aquatic life.
- Full text of classifications [CLP/GHS]** : Aquatic Acute 1, H400 AQUATIC TOXICITY (ACUTE) - Category 1  
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
Org. Perox. B, H241 ORGANIC PEROXIDES - Type B  
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
- Full text of abbreviated R phrases** : R3- Extreme risk of explosion by shock, friction, fire or other sources of ignition.  
R7- May cause fire.  
R36- Irritating to eyes.  
R43- May cause sensitisation by skin contact.  
R50- Very toxic to aquatic organisms.
- Full text of classifications [DSD/DPD]** : E - Explosive  
O - Oxidising  
Xi - Irritant  
N - Dangerous for the environment
- MSDS no.** : 00073827  
**Date of printing** : 8/13/2012.  
**Date of issue/ Date of revision** : 8/13/2012.  
**Date of previous issue** : No previous validation.  
**Version** : 1

Notice to reader

*While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.*

**IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.**

**THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.**

*Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.*

ARALDITE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

**NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.**